WHITEHOUSE
FLEXIBLE TUBING LTD

APOLLO OIL



APOLLO OIL – FLEXIBLE HOSE AND DUCTING

Blue PVC-NBR hose manufactured incorporating a spiral reinforcement of anti-shock rigid PVC.

- Temp Range: -25 to +60°C
- Size Range: 20 - 203mm
- Material: PVC/NBR
- Reinforced: PVC spiral

Apollo Oil Datasheet

PRODUCT DETAILS

WHITEHOUSE
FLEXIBLE TUBING LTD

Apollo Oil

Blue PVC-NBR hose manufactured incorporating a spiral reinforcement of anti-shock rigid PVC.

Application Fields: Suction and delivery of mineral oils, lubricants, crude fuel (naphta, diesel oil) and as a return line in hydraulic systems. AS version with copper wire available on request (cod. OI O2).

Temp Range: -25 to +60°C

Size Range: 20 – 203mm

Material: PVC/NBR

Reinforced: PVC spiral

- Temp Range: -25 to +60°C
- Size Range: 20 – 203mm
- Material: PVC/NBR
- Reinforced: PVC spiral

TECHNICAL DATA

CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING R.	COIL LGTH.	VOLUME
	mm	mm	mm	g/m	bar	bar	m H2O	mm	m	m3
OI010200000000*	20	3,2	3,5	**290**	7	21	10	80	50	0,069
OI010250000000*	25	3,4	3,8	**390**	6	18	10	100	50	0,083
OI010254000000*	25,4	3,4	3,8	**400**	6	18	10	100	50	0,084
OI010320000000*	31,8	4	4,4	**590**	6	18	10	130	50	0,130
OI010380000000*	38,1	3,9	4,5	**670**	5	15	10	155	50	0,203
OI010400000000*	40	3,9	4,5	**700**	5	15	10	160	50	0,212
OI010520000000*	50,8	4,3	4,9	**970**	4	12	10	200	50	0,262
OI010550000000*	55	4,5	5,1	**1100**	4	12	9	220	50	0,376
OI010600000000*	60	4,7	5,4	**1270**	4	12	9	260	50	0,408
OI010630000000*	63,5	4,8	5,5	**1370**	4	12	9	260	50	0,429
OI010700000000*	70	4,9	5,6	**1490**	3	9	9	350	50	0,585
OI010760000000*	76,2	5	5,7	**1660**	3	9	9	310	50	0,631
OI010800000000*	80	5,2	6	**1810**	3	9	9	400	50	0,795
OI010900000000*	90	5,4	6,3	**2110**	3	9	9	360	30	0,591
OI011020000000*	102	6	7,1	**2680**	3	9	8,5	410	30	0,837
OI011270000000*	127	6,4	7,5	**3510**	2,5	7,5	8	510	30	1,091
OI011520000000*	152,4	7,4	8,7	**4930**	2	6	8	610	20	1,358
OI012030000000*	203,2	10,9	12,9	**10010**	1,5	4,5	7	850	10	1,832

DOWNLOADS

Apollo Oil Datasheet

FAQS

What is Apollo Oil?

Blue PVC-NBR hose manufactured incorporating a spiral reinforcement of anti-shock rigid PVC.

What applications are listed for Apollo Oil?

Application Fields: Suction and delivery of mineral oils, lubricants, crude fuel (naphta, diesel oil) and as a return line in hydraulic systems. AS version with copper wire available on request (cod. OI O2).