WHITEHOUSE
FLEXIBLE TUBING LTD

APOLLO SE BLUE



APOLLO SE BLUE – FLEXIBLE HOSE AND DUCTING

Apollo SE Blue suction and delivery hose is particularly suited to use on tank trucks. This heavy duty PVC hose is reinforced with an anti-shock rigid PVC spiral. It is a great product for use at low temperatures. The hose is strong and flexible and resistant to crushing, abrasion, atmospheric agents and most chemicals.

- Colour: Light Blue with Red Stripe.
- Temperature Range: -25°C+60°C

Technical Features : Light Blue PVC hose with an extruded red stripe. It is smooth inside with light corrugation outside.

PRODUCT DETAILS

WHITEHOUSE
FLEXIBLE TUBING LTD

Apollo SE Blue

Apollo SE Blue suction and delivery hose is particularly suited to use on tank trucks. This heavy duty PVC hose is reinforced with an anti-shock rigid PVC spiral. It is a great product for use at low temperatures. The hose is strong and flexible and resistant to crushing, abrasion, atmospheric agents and most chemicals.

Technical Features : Light Blue PVC hose with an extruded red stripe. It is smooth inside with light corrugation outside.

Standards : Antistatic version available on request by manufacture with copper wire.

Application Fields: Excellent solution for suction of liquids in waste management, particularly suitable to be used on tank trucks thanks to its physical-mechanical features.

Colour: Light Blue with Red Stripe.

Temperature Range: -25°C+60°C

*Please note the diameters listed below are all inside diameters . Please check this before ordering.

- Colour: Light Blue with Red Stripe.
- Temperature Range: -25°C+60°C

TECHNICAL DATA

Code	Ins. Ø	Min wall th.	Max. wall th.	Weight	WP	BP	Vac.	Bending	Coil lgth.	Vol.
mm		mm	mm	g/m	bar	bar	m H2O	mm	m	m3
AX 01 019.0 000.0	19,1*	3,2	3,6	290	7	21	10	80	50	0.057
AX 01 020.0 000.0	20*	3,2	3,6	300	7	21	10	80	50	0.059
AX 01 025.0 000.0	25	3,5	3,9	390	6	18	10	100	50	0.082
AX 01 030.0 000.0	30	3,9	4,3	540	6	18	10	120	50	0.124
AX 01 032.0 000.0	31,8	3,9	4,3	570	6	18	10	130	50	0.129
AX 01 035.0 000.0	35*	3,9	4,4	620	5	15	10	140	50	0.140
AX 01 038.0 000.0	38,1	4,0	4,6	670	5	15	10	155	50	0.210
AX 01 040.0 000.0	40	4,0	4,6	700	5	15	10	160	50	0.219
AX 01 045.0 000.0	45*	4,1	4,7	830	4	12	10	180	50	0.243
AX 01 050.0 000.0	50	4,3	4,9	950	4	12	10	200	50	0.343
AX 01 052.0 000.0	50,8	4,3	4,9	970	4	12	10	200	50	0.348
AX 01 055.0 000.0	55*	4,5	5,1	1080	4	12	9	220	50	0.374
AX 01 060.0 000.0	60	4,5	5,6	1210	4	12	9	240	50	0.505
AX 01 063.0 000.0	63,5	4,6	5,7	1370	4	12	9	260	50	0.535
AX 01 065.0 000.0	65*	4,6	5,7	1450	3	9	9	270	50	0.549
AX 01 070.0 000.0	70	4,6	6,1	1560	3	9	9	280	50	0.588
AX 01 076.0 000.0	76,2	4,6	6,2	1750	3	9	9	310	50	0.764
AX 01 080.0 000.0	80	4,6	6,6	1860	3	9	9	320	50	0.800
AX 01 090.0 000.0	90	4,8	6,8	2190	3	9	9	360	30	0.793
AX 01 100.0 000.0	100	5,3	7,6	2830	3	9	85	410	30	0.885

AX 01 102.0 000.0	102	5,3	7,6	2880	3	9	85	410	30	0.900
AX 01 105.0 000.0	105*	5,4	7,7	2990	3	9	85	430	30	0.925
AX 01 110.0 000.0	110	5,5	7,9	3090	3	9	85	450	30	0.963
AX 01 120.0 000.0	120	5,7	8,1	3450	25	75	8	480	30	1.389
AX 01 125.0 000.0	125*	5,7	8,2	3620	25	75	8	500	30	1.442
AX 01 127.0 000.0	127	5,7	8,2	3670	25	75	8	510	30	1.462
AX 01 130.0 000.0	130*	5,8	8,2	4080	25	75	8	530	30	1.501
AX 01 150.0 000.0	151,5	6,6	9,4	4990	2	6	8	610	20	1.353
AX 01 152.0 000.0	152,4	6,6	9,5	5020	2	6	8	610	20	1.360
AX 01 160.0 000.0	160*	7,2	10,2	5500	2	6	7	660	20	1.429
AX 01 200.0 000.0	200*	9,4	13,5	9670	15	45	7	850	10	1.797
AX 01 203.0 000.0	203,2*	9,4	13,4	9810	15	45	7	850	10	1.822
AX 01 250.0 000.0	250*	9,8	14,0	12270	12	37	7	1500	On request	
AX 01 254.0 000.0	254*	9,8	14,0	12460	12	37	7	1500	On request	
AX 01 300.0 000.0	300*	10,0	14,4	15350	1	3	5	1800	On request	
AX 01 305.0 000.0	305*	10,1	14,4	15590	1	3	5	1800	On request	
*Available on request,contact our sales office for more info and quantities										
The technical data here reported were measured at 23°c with 50% humidity										

DOWNLOADS

Apollo SE Blue Datasheet

FAQS

What is Apollo SE Blue?

Apollo SE Blue suction and delivery hose is particularly suited to use on tank trucks. This heavy duty PVC hose is reinforced with an anti-shock rigid PVC spiral. It is a great product for use at low temperatures. The hose is strong and flexible and resistant to crushing, abrasion, atmospheric agents and most chemicals.

What applications are listed for Apollo SE Blue?

Application Fields: Excellent solution for suction of liquids in waste management, particularly suitable to be used on tank trucks thanks to its physical-mechanical features.

What temperature information is given for Apollo SE Blue?

Temperature Range: -25°C+60°C

What colour is Apollo SE Blue?

Colour: Light Blue with Red Stripe.

What technical features are specified for Apollo SE Blue?

Technical Features : Light Blue PVC hose with an extruded red stripe. It is smooth inside with light corrugation outside.

WHITEHOUSE
FLEXIBLE TUBING LTD