

APOLLO SUPERFLEX



Black PVC/NBR hose, reinforced with an anti-shock rigid PVC spiral. Special formulation conceived for keeping the flexibility at extreme temperatures, better than similar PVC hoses commonly used. Antistatic version with copper wire available on request.

Application Fields: Waste Management: suction and discharge of liquids; usually used on tank trunks.

- **Temp Range:** -40 to +50°C
- **Size Range:** 20 - 203mm
- **Material:** PVC/NBR
- **Reinforced:** PVC spiral

[Apollo Superflex Datasheet](#)



WHITEHOUSE

FLEXIBLE TUBING LTD

TECHNICAL DATA

CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM BENDING		COIL LGTH.	VOLUME
	mm	mm	mm	g/m	bar	bar	m H2O	m3	m	m3
AS010200000000*	20	3,2	3,6	300	5	15	10	80	50	0,070
AS010250000000	25	3,4	3,9	400	5	15	10	80	50	0,084
AS010300000000*	30	3,9	4,3	550	5	15	10	100	50	0,124
AS010320000000	31,8	3,9	4,3	580	5	15	10	105	50	0,129
AS010350000000*	35	3,9	4,4	630	4,3	13	10	115	50	0,140
AS010380000000	38,1	3,9	4,4	680	4,3	13	10	125	50	0,180
AS010400000000*	40	3,9	4,4	710	4	12	10	130	50	0,187
AS010450000000*	45	4,1	4,6	840	4	12	10	145	50	0,208
AS010500000000*	50	4,3	4,8	960	3,3	10	10	160	50	0,257
AS010515000000*	51,5	4,3	4,8	990	3,3	10	10	160	50	0,264
AS010520000000	50,8	4,3	4,8	980	3,3	10	10	160	50	0,261
AS010550000000*	55	4,4	5	1090	3,3	10	9	180	50	0,374
AS010570000000*	57	4,4	5	1130	3,3	10	9	190	50	0,386
AS010600000000*	60	4,5	5,1	1220	3,3	10	9	195	50	0,404
AS010630000000	63,5	4,8	5,4	1380	3,3	10	9	210	50	0,428
AS010650000000*	65	4,9	5,6	1460	3	9	9	210	50	0,439
AS010700000000*	70	5	5,8	1570	3	9	9	225	50	0,470
AS010750000000*	75	5	6,1	1740	3	9	9	250	50	0,753
AS010760000000	76,2	5	6,1	1760	3	9	9	250	50	0,764
AS010800000000*	80	5,1	6,3	1880	2,7	8	9	260	50	0,800
AS010900000000*	90	5,3	6,6	2210	2,5	7,5	9	300	30	0,743
AS011000000000*	100	6,1	7,6	2850	2,2	6,5	9	330	30	0,829
AS011020000000	102	6,1	7,6	2910	2,2	6,5	9	335	30	0,844
AS011050000000*	105	6,1	7,7	3020	2	6	9	350	30	0,867
AS011100000000*	110	6,1	7,7	3120	2	6	9	360	30	0,963
AS011200000000*	120	6,3	7,9	3510	1,8	5,5	9	390	30	1,391
AS011270000000	127	6,3	7,9	3700	1,8	5,5	9	410	30	1,462
AS011300000000*	130	7	8,3	4120	1,8	5,5	8	420	30	1,501
AS011500000000*	151,5	7,4	8,8	5030	1,5	4,5	8	500	20	1,299
AS011520000000	152,4	7,4	8,8	5060	1,5	4,5	8	500	20	1,306
AS011600000000*	160	7,9	9,3	5550	1,5	4,5	7	540	20	1,372
AS012000000000*	200	11	12,3	9750	1,2	3,5	7	700	10	0,898
AS012030000000*	203,2	11	12,3	9900	1,2	3,5	7	700	10	0,911

DOWNLOADS

[Apollo Superflex Datasheet](#)



WHITEHOUSE
FLEXIBLE TUBING LTD