

EOLO HT 180°C



Grey duct made with flame resistant TPU coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant V(TM)-0 according to UL 94, grade M1 according NF P 92-503 and in compliance with NF EN 2310, grade FAR25-853-a. Silicon free, it is also free from phthalates and softener.

Application Fields: Civil and naval conditioning plants, ventilation systems, suction of welding fumes, vapours, powders, gas.

- **Temp Range:** -40 to +180°C
- **Size Range:** 40 - 505mm
- **Material:** Polyester fabric coated with self-extinguishing TPU
- **Reinforced:** Steel spiral

[Eolo HT 180 Degrees Datasheet](#)



WHITEHOUSE

FLEXIBLE TUBING LTD

TECHNICAL DATA

CODE	Ø INT. mm	WEIGHT g/m	BENDING mm	COIL LGTH. m	VOL. m3
H1010400000000*	40	125	20	10	0,002
H1010450000000*	45	140	23	10	0,002
H1010510000000*	51	150	26	10	0,003
H1010550000000*	55	165	28	10	0,003
H1010600000000*	60	175	30	10	0,004
H1010630000000*	63	185	32	10	0,004
H1010650000000*	65	190	33	10	0,005
H1010700000000*	70	185	35	10	0,005
H1010760000000*	76	200	38	10	0,006
H1010800000000*	80	210	40	10	0,007
H1010820000000*	82	215	41	10	0,007
H1010900000000*	90	240	45	10	0,009
H1011020000000*	102	310	51	10	0,011
H1011070000000*	107	325	54	10	0,012
H1011100000000*	110	330	55	10	0,013
H1011150000000*	115	345	58	10	0,014
H1011200000000*	120	360	60	10	0,015
H1011270000000*	127	385	64	10	0,017
H1011300000000*	130	390	65	10	0,018
H1011400000000*	140	420	70	10	0,021
H1011520000000*	152	460	76	10	0,024
H1011600000000*	160	470	80	10	0,027
H1011630000000*	163	475	82	10	0,028
H1011800000000*	180	525	90	10	0,034
H1012030000000*	203	595	102	10	0,043
H1012200000000*	220	640	110	10	0,050
H1012280000000*	228	665	114	10	0,054
H1012540000000*	254	910	127	10	0,067
H1012790000000*	279	1000	140	10	0,080
H1013050000000*	305	1095	153	10	0,124
H1013150000000*	315	1130	158	10	0,102
H1013300000000*	330	1180	165	10	0,112
H1013560000000*	356	1275	178	10	0,130
H1014060000000*	406	1455	203	10	0,236
H1015000000000*	500	2015	250	10	0,357
H1015050000000*	505	2035	253	10	0,364

DOWNLOADS

[Eolo HT 180°C](#)



WHITEHOUSE
FLEXIBLE TUBING LTD