WHITEHOUSE
FLEXIBLE TUBING LTD

EOLO HT 180°C



EOLO HT 180°C – FLEXIBLE HOSE AND DUCTING

Grey duct made with flame resistant TPU coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant V(TM)-0 according to UL 94, grade M1 according NF P 92-503 and in compliance with NF EN 2310, grade FAR25-853-a. Silicon free, it is also free from phthalates and softener.

- Temp Range: -40 to +180°C
- Size Range: 40 - 505mm
- Material: Polyester fabric coated with self-extinguishing TPU
- Reinforced: Steel spiral

Eolo HT 180 Degrees Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

Eolo HT 180°C

Grey duct made with flame resistant TPU coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant V(TM)-0 according to UL 94, grade M1 according NF P 92-503 and in compliance with NF EN 2310, grade FAR25-853-a. Silicon free, it is also free from phthalates and softener.

Application Fields: Civil and naval conditioning plants, ventilation systems, suction of welding fumes, vapours, powders, gas.

Temp Range: -40 to +180°C

Size Range: 40 – 505mm

Material: Polyester fabric coated with self-extinguishing TPU

Reinforced: Steel spiral

- Temp Range: -40 to +180°C
- Size Range: 40 – 505mm
- Material: Polyester fabric coated with self-extinguishing TPU
- Reinforced: Steel spiral

TECHNICAL DATA

CODE	Ø INT. mm	WEIGHT g/m	BENDING mm	COIL LGTH. m	VOL. m3
H1010400000000*	40	**125**	20	10	0,002
H1010450000000*	45	**140**	23	10	0,002
H1010510000000*	51	**150**	26	10	0,003
H1010550000000*	55	**165**	28	10	0,003
H1010600000000*	60	**175**	30	10	0,004
H1010630000000*	63	**185**	32	10	0,004
H1010650000000*	65	**190**	33	10	0,005
H1010700000000*	70	**185**	35	10	0,005
H1010760000000*	76	**200**	38	10	0,006
H1010800000000*	80	**210**	40	10	0,007
H1010820000000*	82	**215**	41	10	0,007
H1010900000000*	90	**240**	45	10	0,009
H1011020000000*	102	**310**	51	10	0,011
H1011070000000*	107	**325**	54	10	0,012
H1011100000000*	110	**330**	55	10	0,013
H1011150000000*	115	**345**	58	10	0,014
H1011200000000*	120	**360**	60	10	0,015
H1011270000000*	127	**385**	64	10	0,017
H1011300000000*	130	**390**	65	10	0,018
H1011400000000*	140	**420**	70	10	0,021
H1011520000000*	152	**460**	76	10	0,024

H1011600000000*	160	**470**	80	10	0,027
H1011630000000*	163	**475**	82	10	0,028
H1011800000000*	180	**525**	90	10	0,034
H1012030000000*	203	**595**	102	10	0,043
H1012200000000*	220	**640**	110	10	0,050
H1012280000000*	228	**665**	114	10	0,054
H1012540000000*	254	**910**	127	10	0,067
H1012790000000*	279	**1000**	140	10	0,080
H1013050000000*	305	**1095**	153	10	0,124
H1013150000000*	315	**1130**	158	10	0,102
H1013300000000*	330	**1180**	165	10	0,112
H1013560000000*	356	**1275**	178	10	0,130
H1014060000000*	406	**1455**	203	10	0,236
H1015000000000*	500	**2015**	250	10	0,357
H1015050000000*	505	**2035**	253	10	0,364

DOWNLOADS

Eolo HT 180°C

FAQS

What is Eolo HT 180°C?

Grey duct made with flame resistant TPU coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant V(TM)-0 according to UL 94, grade M1 according NF P 92-503 and in compliance with NF EN 2310, grade FAR25-853-a. Silicon free, it is also free from phthalates and softener.

What applications are listed for Eolo HT 180°C?

Application Fields: Civil and naval conditioning plants, ventilation systems, suction of welding fumes, vapours, powders, gas.

What else does the product description state about Eolo HT 180°C?

Material: Polyester fabric coated with self-extinguishing TPU