

## EOLO HT 180°C



Grey duct made with flame resistant TPU coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant V(TM)-0 according to UL 94, grade M1 according NF P 92-503 and in compliance with NF EN 2310, grade FAR25-853-a. Silicon free, it is also free from phthalates and softener.

**Application Fields:** Civil and naval conditioning plants, ventilation systems, suction of welding fumes, vapours, powders, gas.

- **Temp Range:** -40 to +180°C
- **Size Range:** 40 - 505mm
- **Material:** Polyester fabric coated with self-extinguishing TPU
- **Reinforced:** Steel spiral

[Eolo HT 180 Degrees Datasheet](#)



# WHITEHOUSE

FLEXIBLE TUBING LTD

## TECHNICAL DATA

| CODE            | Ø INT.<br>mm | WEIGHT<br>g/m | BENDING<br>mm | COIL LGTH.<br>m | VOL.<br>m <sup>3</sup> |
|-----------------|--------------|---------------|---------------|-----------------|------------------------|
| H1010400000000* | 40           | 125           | 20            | 10              | 0,002                  |
| H1010450000000* | 45           | 140           | 23            | 10              | 0,002                  |
| H1010510000000* | 51           | 150           | 26            | 10              | 0,003                  |
| H1010550000000* | 55           | 165           | 28            | 10              | 0,003                  |
| H1010600000000* | 60           | 175           | 30            | 10              | 0,004                  |
| H1010630000000* | 63           | 185           | 32            | 10              | 0,004                  |
| H1010650000000* | 65           | 190           | 33            | 10              | 0,005                  |
| H1010700000000* | 70           | 185           | 35            | 10              | 0,005                  |
| H1010760000000* | 76           | 200           | 38            | 10              | 0,006                  |
| H1010800000000* | 80           | 210           | 40            | 10              | 0,007                  |
| H1010820000000* | 82           | 215           | 41            | 10              | 0,007                  |
| H1010900000000* | 90           | 240           | 45            | 10              | 0,009                  |
| H1011020000000* | 102          | 310           | 51            | 10              | 0,011                  |
| H1011070000000* | 107          | 325           | 54            | 10              | 0,012                  |
| H1011100000000* | 110          | 330           | 55            | 10              | 0,013                  |
| H1011150000000* | 115          | 345           | 58            | 10              | 0,014                  |
| H1011200000000* | 120          | 360           | 60            | 10              | 0,015                  |
| H1011270000000* | 127          | 385           | 64            | 10              | 0,017                  |
| H1011300000000* | 130          | 390           | 65            | 10              | 0,018                  |
| H1011400000000* | 140          | 420           | 70            | 10              | 0,021                  |
| H1011520000000* | 152          | 460           | 76            | 10              | 0,024                  |
| H1011600000000* | 160          | 470           | 80            | 10              | 0,027                  |
| H1011630000000* | 163          | 475           | 82            | 10              | 0,028                  |
| H1011800000000* | 180          | 525           | 90            | 10              | 0,034                  |
| H1012030000000* | 203          | 595           | 102           | 10              | 0,043                  |
| H1012200000000* | 220          | 640           | 110           | 10              | 0,050                  |
| H1012280000000* | 228          | 665           | 114           | 10              | 0,054                  |
| H1012540000000* | 254          | 910           | 127           | 10              | 0,067                  |
| H1012790000000* | 279          | 1000          | 140           | 10              | 0,080                  |
| H1013050000000* | 305          | 1095          | 153           | 10              | 0,124                  |
| H1013150000000* | 315          | 1130          | 158           | 10              | 0,102                  |
| H1013300000000* | 330          | 1180          | 165           | 10              | 0,112                  |
| H1013560000000* | 356          | 1275          | 178           | 10              | 0,130                  |
| H1014060000000* | 406          | 1455          | 203           | 10              | 0,236                  |
| H1015000000000* | 500          | 2015          | 250           | 10              | 0,357                  |
| H1015050000000* | 505          | 2035          | 253           | 10              | 0,364                  |

## DOWNLOADS

[Eolo HT 180°C](#)



**WHITEHOUSE**  
FLEXIBLE TUBING LTD