WHITEHOUSE
FLEXIBLE TUBING LTD

IPL EOLO PUP EST



IPL EOLO PUP EST – FLEXIBLE HOSE AND DUCTING

IPL Eolo PUP EST is a transparent ester based TPU hose, reinforced with a dark grey anti-shock rigid PVC spiral. Wall thickness from 0,8 mm to 1,0 mm. Specifically compounded for abrasive media, it maintains high flexibility even at low temperature. Inner surface completely smooth to maximise optimal flow. Resistant to abrasion and torsion.

- Temp Range: -40 to +80°C
- Size Range: 30 - 254mm
- Material: TPU with ester base
- Reinforced: PVC spiral

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

IPL Eolo PUP EST

IPL Eolo PUP EST Flexible Ducting / Flexible Hose

IPL Eolo PUP EST is a transparent ester based TPU hose, reinforced with a dark grey anti-shock rigid PVC spiral. Wall thickness from 0,8 mm to 1,0 mm. Specifically compounded for abrasive media, it maintains high flexibility even at low temperature. Inner surface completely smooth to maximise optimal flow. Resistant to abrasion and torsion.

Application Fields: Suction and delivery of abrasive media such as pellets and granulates. It finds optimal application in the plastic and ceramic Industry. Can be used in woodworking under severe conditions. On request it can be manufactured with copper wire for earthing to protect against static dissipation.

Temp Range: -40 to +80°C

Size Range: 30 – 254mm

Material: TPU with ester base

Reinforced: PVC spiral

- Temp Range: -40 to +80°C
- Size Range: 30 – 254mm
- Material: TPU with ester base
- Reinforced: PVC spiral

TECHNICAL DATA

CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm	mm	mm	g/m	m H2O	mm	m	m3
OP010300000000*	30	0,8	3,3	**260**	3,5	100	30	0,07
OP010320000000*	31,8	0,8	3,3	**280**	3	110	30	0,07
OP010350000000*	35	0,8	3,5	**310**	3	120	30	0,08
OP010380000000	38,1	0,8	3,5	**330**	3	130	30	0,09
OP010390000000*	39	0,8	3,5	**340**	3	135	30	0,12
OP010400000000	40	1	3,6	**380**	3	140	30	0,12
OP010450000000	45	1	3,9	**480**	3	160	30	0,15
OP010500000000*	50	1	4,3	**590**	3	175	30	0,17
OP010520000000	50,8	1	4,3	**600**	3	175	30	0,17
OP010600000000	60	1	4,3	**700**	3	200	30	0,30
OP010630000000	63,5	1	4,3	**730**	3	230	30	0,31
OP010650000000*	65	1	4,3	**750**	3	230	30	0,32
OP010700000000	70	1	4,8	**820**	3	250	30	0,34
OP010760000000	76,2	1	4,8	**890**	2,5	270	30	0,37
OP010800000000	80	1	5,2	**990**	2,5	290	30	0,39
OP010900000000	90	1	5,4	**1170**	2,5	360	30	0,58

OP011000000000	100	1	5,9	**1360**	2,5	400	30	0,64
OP011020000000	102	1	5,9	**1390**	2,5	400	30	0,66
OP011100000000*	110	1	6,1	**1510**	2,5	440	30	0,70
OP011200000000	120	1	6,1	**1640**	2,5	470	30	1,02
OP011270000000*	127	1	6,1	**1730**	2,5	500	30	1,07
OP011300000000*	130	1	6,1	**1770**	2,5	520	30	1,09
OP011400000000*	140	1	6,2	**1950**	2	570	30	1,56
OP011500000000*	151,5	1	6,6	**2170**	2	600	20	1,26
OP011520000000*	152,4	1	6,6	**2180**	2	600	20	1,27
OP012540000000*	254	1,2	9,4	**4030**	1	500	10	1,40

DOWNLOADS

Eolo PUP EST Datasheet

IPL Eolo PUP EST is a transparent ester based TPU hose, reinforced with a dark grey anti-shock rigid PVC spiral. It is a similar product to Merlett Oregon PUP EST Antistatico.

FAQS

What is IPL Eolo PUP EST?

IPL Eolo PUP EST is a transparent ester based TPU hose, reinforced with a dark grey anti-shock rigid PVC spiral. Wall thickness from 0,8 mm to 1,0 mm. Specifically compounded for abrasive media, it maintains high flexibility even at low temperature. Inner surface completely smooth to maximise optimal flow. Resistant to abrasion and torsion.

What applications are listed for IPL Eolo PUP EST?

Application Fields: Suction and delivery of abrasive media such as pellets and granulates. It finds optimal application in the plastic and ceramic Industry. Can be used in woodworking under severe conditions. On request it can be manufactured with copper wire for earthing to protect against static dissipation.

What else does the product description state about IPL Eolo PUP EST?

IPL Eolo PUP EST Flexible Ducting / Flexible Hose