WHITEHOUSE
FLEXIBLE TUBING LTD

EOLO SL

Light blue plasticized PVC duct reinforced with anti-shock rigid PVC spiral. Perfectly smooth inside, outside corrugated. The lightest and most flexible of the range. Resistant to low temperatures.

Application Fields: Suction of air, fumes, gas. Conditioning, aeration.

- **Temp Range:** -10 to +50°C
- **Size Range:** 25 - 203mm
- **Material:** Plasticized PVC
- **Reinforced:** PVC spiral

Eolo SL Blue Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

TECHNICAL DATA

CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm/inch	mm	mm	g/m	m H2O	mm	m	m3
ES010250000000	25	0,6	2,5	**140**	0,8	30	30	0,039
ES010270000000	27	0,6	2,5	**150**	0,8	40	30	0,052
ES010300000000	30	0,6	2,5	**160**	0,8	40	30	0,061
ES010320000000	31,8	0,7	2,5	**180**	0,7	40	30	0,061
ES010350000000	35	0,7	2,6	**200**	0,7	40	30	0,087
ES010380000000	38,1	0,7	2,6	**210**	0,7	50	30	0,094
ES010390000000*	39	0,7	2,7	**230**	0,7	55	30	0,112
ES010400000000	40	0,7	2,7	**230**	0,7	50	30	0,114
ES010450000000	45	0,7	2,7	**260**	0,7	80	30	0,145
ES010500000000	50	0,7	2,9	**300**	0,7	90	30	0,161
ES010515000000*	51,5	0,7	2,9	**310**	0,7	90	30	0,165
ES010520000000	50,8	0,7	2,9	**310**	0,7	90	30	0,163
ES010550000000*	55	0,7	3,1	**360**	0,7	95	30	0,176
ES010600000000	60	0,7	3,4	**440**	0,6	100	30	0,192
ES010630000000	63,5	0,7	3,5	**490**	0,6	100	30	0,203
ES010650000000*	65	0,7	3,5	**500**	0,6	100	30	0,311
ES010700000000	70	0,7	3,8	**520**	0,5	110	30	0,335
ES010760000000	76,2	0,7	3,8	**560**	0,5	120	30	0,362
ES010777000000*	77,7	0,7	3,8	**570**	0,5	120	30	0,368
ES010800000000	80	0,8	4	**620**	0,5	130	30	0,380
ES010900000000*	90	0,8	4,1	**720**	0,4	150	30	0,424
ES011000000000	100	0,8	4,3	**800**	0,4	160	30	0,626
ES011020000000	102	0,8	4,3	**810**	0,4	160	30	0,637
ES011035000000*	103,5	0,8	4,3	**820**	0,4	170	30	0,646
ES011100000000	110	0,8	4,7	**950**	0,4	190	30	0,688
ES011200000000	120	0,8	4,8	**1060**	0,4	200	30	0,746
ES011270000000	127	0,8	4,9	**1160**	0,3	230	30	0,985
ES011300000000*	130	0,8	5,1	**1260**	0,3	250	30	1,009
ES011400000000*	140	0,8	5,1	**1360**	0,3	260	30	1,081
ES011500000000	151,5	0,9	5,5	**1580**	0,3	280	20	0,936
ES011520000000	152,4	0,9	5,6	**1630**	0,3	280	20	0,942
ES011600000000*	160	1	6,1	**1770**	0,2	280	20	0,992
ES011800000000*	180	1	6,1	**1980**	0,2	450	20	1,476
ES012000000000*	200	1	6,6	**2310**	0,2	600	20	1,637
ES012030000000*	203,2	1	6,6	**2350**	0,2	600	20	1,662

DOWNLOADS

Eolo SL

WHITEHOUSE
FLEXIBLE TUBING LTD