WHITEHOUSE
FLEXIBLE TUBING LTD

EOLO TERMORESISTENTE

EOLO TERMORESISTENTE – FLEXIBLE HOSE AND DUCTING

Grey flexible duct made with flame resistant PVC coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant, according to UL 94 V(TM)-0 and to NFP 92 503 (grade M2). Axial compressibility: 8:1.

- Temp Range: -20 to +100°C
- Size Range: 40 - 505mm
- Material: Polyester fabric coated with self-extinguishing PVC
- Reinforced: Steel spiral

Eolo Termoresistente Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

Eolo Termoresistente

Grey flexible duct made with flame resistant PVC coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant, according to UL 94 V(TM)-0 and to NFP 92 503 (grade M2). Axial compressibility: 8:1.

Application Fields: Civil and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders, gas.

Temp Range: -20 to +100°C

Size Range: 40 – 505mm

Material: Polyester fabric coated with self-extinguishing PVC

Reinforced: Steel spiral

- Temp Range: -20 to +100°C
- Size Range: 40 – 505mm
- Material: Polyester fabric coated with self-extinguishing PVC
- Reinforced: Steel spiral

TECHNICAL DATA

CODE	Ø INT. mm	WEIGHT g/m	BENDING mm	COIL LGTH. m	VOL. m3
TR010400000000	40	**115**	20	10	0,002
TR010450000000*	45	**125**	23	10	0,002
TR010510000000	51	**135**	26	10	0,003
TR010550000000*	55	**145**	28	10	0,003
TR010600000000	60	**160**	30	10	0,004
TR010630000000	63	**165**	32	10	0,004
TR010650000000*	65	**170**	33	10	0,005
TR010700000000	70	**165**	35	10	0,005
TR010730000000*	73	**175**	37	10	0,006
TR010760000000	76	**180**	38	10	0,006
TR010800000000	80	**190**	40	10	0,007
TR010820000000*	82	**195**	41	10	0,007
TR010900000000	90	**210**	45	10	0,009
TR011020000000	102	**275**	51	10	0,011
TR011070000000*	107	**290**	54	10	0,012
TR011100000000	110	**300**	55	10	0,013
TR011150000000	115	**310**	58	10	0,014
TR011200000000	120	**325**	60	10	0,015
TR011250000000*	125	**340**	63	10	0,016
TR011270000000	127	**345**	64	10	0,017
TR011300000000	130	**350**	65	10	0,018
TR011400000000	140	**380**	70	10	0,021

TR011520000000	152	**410**	76	10	0,024
TR011600000000	160	**420**	80	10	0,027
TR011630000000*	163	**430**	82	10	0,028
TR011700000000*	170	**445**	85	10	0,030
TR011800000000	180	**475**	90	10	0,034
TR012000000000*	200	**525**	100	10	0,041
TR012030000000	203	**535**	102	10	0,043
TR012280000000	228	**600**	114	10	0,054
TR012300000000*	230	**600**	115	10	0,055
TR012540000000	254	**840**	127	10	0,067
TR012790000000*	279	**920**	140	10	0,080
TR013050000000	305	**1005**	153	10	0,124
TR013100000000*	310	**1020**	155	10	0,099
TR013150000000*	315	**1040**	158	10	0,102
TR013300000000*	330	**1090**	165	10	0,112
TR013560000000	356	**1175**	178	10	0,130
TR014060000000	406	**1335**	203	10	0,168
TR014550000000*	455	**1875**	228	10	0,211
TR015000000000*	500	**2055**	250	10	0,255
TR015050000000*	505	**2080**	253	10	0,260

DOWNLOADS

Eolo Termoresistente

FAQS

What is Eolo Termoresistente?

Grey flexible duct made with flame resistant PVC coated polyester fabric and reinforced by steel helix welded between the two layers. The material is flame retardant, according to UL 94 V(TM)-0 and to NFP 92 503 (grade M2). Axial compressibility: 8:1.

What applications are listed for Eolo Termoresistente?

Application Fields: Civil and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders, gas.

What else does the product description state about Eolo Termoresistente?

Material: Polyester fabric coated with self-extinguishing PVC