WHITEHOUSE
FLEXIBLE TUBING LTD

EOLO VENT



EOLO VENT – FLEXIBLE HOSE AND DUCTING

Grey hose made in flame retardant PVC coated with polyester fabric, reinforced with a steel wire. The steel helix is welded between 2 fabric layers. Axial compressibility 8:1.

- Temp Range: -20 to +100°c
- Size Range: 40 - 406mm
- Material: PVC coated with polyester fabric
- Reinforced: Steel spiral

Eolo Vent Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

Eolo Vent

Grey hose made in flame retardant PVC coated with polyester fabric, reinforced with a steel wire. The steel helix is welded between 2 fabric layers. Axial compressibility 8:1.

Application Fields: Industrial and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders and gas.

Temp Range: -20 to +100°c

Size Range: 40 – 406mm

Material: PVC coated with polyester fabric

Reinforced: Steel spiral

- Temp Range: -20 to +100°c
- Size Range: 40 – 406mm
- Material: PVC coated with polyester fabric
- Reinforced: Steel spiral

TECHNICAL DATA

Code	Ins. Ø mm	Weight g/m	Bending mm	Coil lgth. m	Vol. m3
TO 01 040.0 000.0	**40**	**70**	**20**	**6-10**	**0,002**
TO 01 051.0 000.0	**51**	**95**	**26**	**6-10**	**0,003**
TO 01 060.0 000.0	**60**	**115**	**30**	**6-10**	**0,004**
TO 01 063.0 000.0	**63**	**118**	**32**	**6-10**	**0,005**
TO 01 070.0 000.0	**70**	**120**	**35**	**6-10**	**0,006**
TO 01 076.0 000.0	**76**	**130**	**38**	**6-10**	**0,006**
TO 01 080.0 000.0	**80**	**140**	**40**	**6-10**	**0,007**
TO 01 090.0 000.0	**90**	**155**	**45**	**6-10**	**0,009**
TO 01 102.0 000.0	**102**	**135**	**51**	**6-10**	**0,011**
TO 01 110.0 000.0	**110**	**145**	**55**	**6-10**	**0,013**
TO 01 115.0 000.0	**115**	**155**	**58**	**6-10**	**0,014**
TO 01 120.0 000.0	**120**	**160**	**60**	**6-10**	**0,015**
TO 01 127.0 000.0	**127**	**170**	**64**	**6-10**	**0,017**
TO 01 130.0 000.0	**130**	**175**	**65**	**6-10**	**0,018**
TO 01 140.0 000.0	**140**	**185**	**70**	**6-10**	**0,021**
TO 01 152.0 000.0	**152**	**200**	**76**	**6-10**	**0,024**
TO 01 160.0 000.0	**160**	**210**	**80**	**6-10**	**0,027**
TO 01 180.0 000.0	**180**	**240**	**90**	**6-10**	**0,034**
TO 01 203.0 000.0	**203**	**270**	**102**	**6-10**	**0,043**
TO 01 228.0 000.0	**228**	**300**	**114**	**6-10**	**0,054**
TO 01 254.0 000.0	**254**	**335**	**127**	**6-10**	**0,067**

TO 01 279.0 000.0	**279**	**365**	**140**	**6-10**	**0,080**
TO 01 305.0 000.0	**305**	**400**	**153**	**6-10**	**0,096**
TO 01 315.0 000.0	**315**	**415**	**158**	**6-10**	**0,102**
TO 01 330.0 000.0	**330**	**430**	**165**	**6-10**	**0,112**
TO 01 356.0 000.0	**356**	**470**	**178**	**6-10**	**0,130**
TO 01 406.0 000.0	**406**	**530**	**203**	**6-10**	**0,168**

*Available on request,contact our sales office for more info and quantities
The technical data here reported were measured at 23°c with 50% humidity

DOWNLOADS

Eolo Vent Datasheet

FAQS

What is Eolo Vent?

Grey hose made in flame retardant PVC coated with polyester fabric, reinforced with a steel wire. The steel helix is welded between 2 fabric layers. Axial compressibility 8:1.

What applications are listed for Eolo Vent?

Application Fields: Industrial and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders and gas.