

EOLO VENT



Grey hose made in flame retardant PVC coated with polyester fabric, reinforced with a steel wire. The steel helix is welded between 2 fabric layers. Axial compressibility 8:1.

Application Fields: Industrial and naval conditioning plants, ventilation systems, suction of fumes, vapours, powders and gas.

- **Temp Range:** -20 to +100°C
- **Size Range:** 40 - 406mm
- **Material:** PVC coated with polyester fabric
- **Reinforced:** Steel spiral

[Eolo Vent Datasheet](#)



WHITEHOUSE FLEXIBLE TUBING LTD

TECHNICAL DATA

Code	Ins. Ø mm	Weight g/m	Bending mm	Coil lgth. m	Vol. m ³
TO 01 040.0 000.0	40	70	20	6-10	0,002
TO 01 051.0 000.0	51	95	26	6-10	0,003
TO 01 060.0 000.0	60	115	30	6-10	0,004
TO 01 063.0 000.0	63	118	32	6-10	0,005
TO 01 070.0 000.0	70	120	35	6-10	0,006
TO 01 076.0 000.0	76	130	38	6-10	0,006
TO 01 080.0 000.0	80	140	40	6-10	0,007
TO 01 090.0 000.0	90	155	45	6-10	0,009
TO 01 102.0 000.0	102	135	51	6-10	0,011
TO 01 110.0 000.0	110	145	55	6-10	0,013
TO 01 115.0 000.0	115	155	58	6-10	0,014
TO 01 120.0 000.0	120	160	60	6-10	0,015
TO 01 127.0 000.0	127	170	64	6-10	0,017
TO 01 130.0 000.0	130	175	65	6-10	0,018
TO 01 140.0 000.0	140	185	70	6-10	0,021
TO 01 152.0 000.0	152	200	76	6-10	0,024
TO 01 160.0 000.0	160	210	80	6-10	0,027
TO 01 180.0 000.0	180	240	90	6-10	0,034
TO 01 203.0 000.0	203	270	102	6-10	0,043
TO 01 228.0 000.0	228	300	114	6-10	0,054
TO 01 254.0 000.0	254	335	127	6-10	0,067
TO 01 279.0 000.0	279	365	140	6-10	0,080
TO 01 305.0 000.0	305	400	153	6-10	0,096
TO 01 315.0 000.0	315	415	158	6-10	0,102
TO 01 330.0 000.0	330	430	165	6-10	0,112
TO 01 356.0 000.0	356	470	178	6-10	0,130
TO 01 406.0 000.0	406	530	203	6-10	0,168

*Available on request,contact our sales office for more info and quantities
The technical data here reported were measured at 23°C with 50% humidity

DOWNLOADS

[Eolo Vent Datasheet](#)