WHITEHOUSE
FLEXIBLE TUBING LTD

IPL GREEN MDS



IPL GREEN MDS – FLEXIBLE HOSE AND DUCTING

This medium duty green suction and delivery hose is a PVC reinforced hose which is particularly suited to be used at low temperatures. The super-elastic hose has high mechanical properties and offers flexibility, a good bend radius, resistance to torsion, crushing, ageing, ozone, hydrolysis and most chemicals.

- Colour: Green
- Temperature Range: -25°C +60°C

Technical features : PVC hose reinforced with an anti-shock rigid PVC spiral. Completely free from phthalates with smooth bore, slightly corrugated outside.

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

IPL Green MDS

This medium duty green suction and delivery hose is a PVC reinforced hose which is particularly suited to be used at low temperatures. The super-elastic hose has high mechanical properties and offers flexibility, a good bend radius, resistance to torsion, crushing, ageing, ozone, hydrolysis and most chemicals.

Technical features : PVC hose reinforced with an anti-shock rigid PVC spiral. Completely free from phthalates with smooth bore, slightly corrugated outside.

Application Fields: Suction of liquids, slurry and delivery, particularly suitable to be used on tank trucks thanks to its physical-mechanical features.

Colour: Green

Temperature Range: -25°C +60°C

*Please note the diameters listed below are all inside diameters . Please check this before ordering.

- Colour: Green
- Temperature Range: -25°C +60°C

TECHNICAL DATA

Code	Ins. Ø	Min wall th.	Max. wall th.	Weight	WP	BP	Vac.	Bending	Coil lgth.	Vol.
	mm	mm	mm	g/m	bar	bar	m H_2O	mm	m	m_3
NX NF 025.0 000.0	25	2.7	3.0	310	3.3	10	5	110	30	0.085
NX NF 032.0 000.0	31.8	2.8	3.1	400	3.3	10	5	140	30	0.128
NX NF 038.0 000.0	38.1	3.0	3.5	520	3.3	10	5	160	30	0.183
NX NF 052.0 000.0	50.8	3.4	4.2	820	3.3	10	5	200	30	0.297
NX NF 063.0 000.0	63.5	3.5	4.3	1060	3.3	10	5	250	30	0.488
NX NF 076.0 000.0	76.2	3.9	4.9	1400	3.3	10	5	290	30	0.655
NX NF 102.0 000.0	102	48	6.0	2280	3.0	9	5	400	30	0.729
NX NF 127.0 000.0	127	5.2	6.5	3040	2.0	6	3	580	20/30	1.130
NX NF 150.0 000.0	151.5	6.2	7.7	4350	2.0	6	3	660	20/30	1.282
*Available on request,contact our sales office for more info and quantities										
The technical data here reported were measured at 23°c with 50% humidity										

DOWNLOADS

IPL Green MDS Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

FAQS

What is IPL Green MDS?

This medium duty green suction and delivery hose is a PVC reinforced hose which is particularly suited to be used at low temperatures. The super-elastic hose has high mechanical properties and offers flexibility, a good bend radius, resistance to torsion, crushing, ageing, ozone, hydrolysis and most chemicals.

What applications are listed for IPL Green MDS?

Application Fields: Suction of liquids, slurry and delivery, particularly suitable to be used on tank trucks thanks to its physical-mechanical features.

What temperature information is given for IPL Green MDS?

Temperature Range: -25°C +60°C

What colour is IPL Green MDS?

Colour: Green

What technical features are specified for IPL Green MDS?

Technical features : PVC hose reinforced with an anti-shock rigid PVC spiral. Completely free from phthalates with smooth bore, slightly corrugated outside.