WHITEHOUSE
FLEXIBLE TUBING LTD

NAUTILUS ODORPROOF

White PVC-P hose reinforced with an anti-shock rigid PVC spiral. Special odourless formulation against permeation of smells. Inside and outside completely smooth to enhance the flow properties; crash proof and very flexible.

Application Fields: Waste disposal, suction and discharge of liquids, specially used on marine sanitation systems.

- **Temp Range:** -10 to +60°C
- **Size Range:** 16 - 51mm
- **Material:** PVC-P
- **Reinforced:** PVC-U spiral

Nautilus Odorproof Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

TECHNICAL DATA

CODE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOL.
	mm	mm	mm	g/m	bar	bar	m H2O	mm	m	m3
LU010160021000*	16	2,4	2,6	**180**	8	24	9	78	30	0,031
LU010200025000	20	2,4	2,6	**220**	8	24	9	78	30	0,036
LU010250031000	25	2,9	3,1	**340**	6	18	9	102	30	0,056
LU010300036500*	30	3	3,2	**420**	6	18	9	102	30	0,092
LU010320038500*	31,8	3	3,2	**440**	6	18	9	102	30	0,096
LU010380046000	38,1	3,9	4,1	**690**	6	18	9	190	30	0,119
LU010400048000*	40	3,9	4,1	**720**	6	18	9	190	30	0,123
LU010500061000	50	5,3	5,5	**1250**	6	18	9	190	30	0,264
LU010508061800*	50,8	5,3	5,5	**1270**	6	18	9	190	30	0,267

DOWNLOADS

Nautilus Odorproof Datasheet