



WHITEHOUSE
FLEXIBLE TUBING LTD

NETTUNO



Nettuno is a total food grade hose made with a plasticized vinyl compound and reinforced with an anti-shock rigid PVC spiral. It is a light weight and highly flexible suction and delivery hose. This product is resistant to atmospheric agents and a wide range of chemicals. An antistatic version is available on request.

Technical Features: Transparent PVC hose with an ivory anti-shock rigid PVC spiral. It is smooth inside to ensure optimization of flow properties. Food grade hose wall.

Standards: Food grade according to EU Regulation 10/2011 (Classes A, B, C, D1). The antistatic version with copper wire is available upon request.

Application Fields: This is an ideal solution for suction and delivery of food powders like flours, light grains, freeze dried foodstuffs as well as for liquid in general, beverages, juices, vinegar, wines and liquor with alcohol concentration up to 50%. Suitable for delivery of milk and by-products.

- **Colour:** Transparent with ivory plastic spiral.
- **Temperature Range:** -10°C+60°C

*Please note the diameters listed below are all **inside diameters**. Please check this before ordering.



WHITEHOUSE

FLEXIBLE TUBING LTD

TECHNICAL DATA

Code	Ins. Ø	Min wall th.	Max. wall th.	Weight	WP	BP	Vac.	Bending	Coil lgth.	Vol.
	mm	mm	mm	g/m	bar	bar	m	mm	m	m ³
NQ 01 013.0 000.0	13	2.4	2.7	150	10	30	7	75	50	0.040
NQ 01 016.0 000.0	16	2.5	2.8	190	8	24	7	90	50	0.047
NQ 01 019.0 000.0	19.1*	2.6	2.9	230	7	21	7	110	50	0.054
NQ 01 020.0 000.0	20	2.6	2.9	240	7	21	7	110	50	0.056
NQ 01 025.0 000.0	25	2.6	2.9	290	6	18	7	130	50	0.078
NQ 01 030.0 000.0	30	2.7	3	360	5	15	7	150	50	0.115
NQ 01 032.0 000.0	31.8	2.7	3	380	5	15	7	155	50	0.121
NQ 01 035.0 000.0	35	2.7	3.2	440	4	12	7	170	50	0.161
NQ 01 038.0 000.0	38.1	2.9	3.5	510	4	12	7	180	50	0.175
NQ 01 040.0 000.0	40	3	3.5	560	4	12	7	195	50	0.183
NQ 01 045.0 000.0	45	3.2	3.8	680	4	12	7	215	50	0.238
NQ 01 050.0 000.0	50	3.3	4.2	810	4	12	7	235	50	0.264
NQ 01 052.0 000.0	50.8	3.3	4.2	820	4	12	7	235	50	0.268
NQ 01 055.0 000.0	55*	3.4	4.3	910	4	12	7	255	50	0.370
NQ 01 060.0 000.0	60	3.4	4.2	990	4	12	7	275	50	0.498
NQ 01 063.0 000.0	63.5	3.4	4.3	1060	4	12	7	290	50	0.525
NQ 01 065.0 000.0	65*	3.5	4.4	1120	4	12	7	300	50	0.537
NQ 01 070.0 000.0	70	3.7	4.6	1220	3	9	7	320	50	0.691
NQ 01 076.0 000.0	76.2	3.9	4.8	1400	3	9	7	340	50	0.748
NQ 01 080.0 000.0	80	4.2	5.2	1550	3	9	7	365	50	0.932
NQ 01 090.0 000.0	90	4.4	5.5	1860	3	9	7	420	30	0.782
NQ 01 100.0 000.0	100	4.8	60	2240	3	9	7	470	30	0.866
NQ 01 102.0 000.0	102	4.8	6	2280	3	9	7	470	30	0.882
NQ 01 110.0 000.0	110	5	6.3	2560	3	9	6	520	30	1.264
NQ 01 120.0 000.0	120	5.1	6.4	2840	3	9	6	650	30	1.069
NQ 01 127.0 000.0	127	5.2	6.5	3060	3	9	5.5	680	30	1.690
NQ 01 150.0 000.0	151.5	6.1	7.6	4390	3	9	5	780	20	1.343
NQ 01 152.0 000.0	152.8*	6.1	7.6	4420	3	9	5	780	20	1.354
NQ 01 200.0 000.0	200*	6.5	9.3	6520	2	6	4.5	1000	10	2.130
NQ 01 203.0 000.0	203.2*	6.5	9.3	6620	2	6	4.5	1000	10	2.161
NQ 01 250.0 000.0	250*	6.8	9.7	8600	1.5	4.5	4	1800	on request	
NQ 01 254.0 000.0	254*	6.8	9.7	8730	1.5	4.5	4	1800	on request	
NQ 01 300.0 000.0	300*	7.2	10.3	11030	1	3	4	2000	on request	
NQ 01 305.0 000.0	305*	7.2	10.3	11200	1	3	4	2000	on request	

*Available on request, contact our sales office for more info and quantities

The technical data here reported were measured at 23°C with 50% humidity



WHITEHOUSE
FLEXIBLE TUBING LTD

DOWNLOADS

[Nettuno Datasheet](#)

[FOOD CONTACT DECLARATION](#)