WHITEHOUSE
FLEXIBLE TUBING LTD

PLUTONE PW



PLUTONE PW – FLEXIBLE HOSE AND DUCTING

Black hose with yellow stripe made by a special PVC-P compound, with steel helix and polyester textile reinforcement. Smooth, flexible and easy to handle, it resists at low temperatures. It can be made conductive (R<102 Ohm/m) by grounding the spiral.

- Temp Range: -25 to +60°C
- Size Range: 20 - 102mm
- Material: PVC-P
- Reinforced: Polyester textile & steel spiral

Plutone PW Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

Plutone PW

Black hose with yellow stripe made by a special PVC-P compound, with steel helix and polyester textile reinforcement. Smooth, flexible and easy to handle, it resists at low temperatures. It can be made conductive (R<102 Ohm/m) by grounding the spiral.

Application Fields: Suction and discharge of water and liquids.

Temp Range: -25 to +60°C

Size Range: 20 – 102mm

Material: PVC-P

Reinforced: Polyester textile & steel spiral

- Temp Range: -25 to +60°C
- Size Range: 20 – 102mm
- Material: PVC-P
- Reinforced: Polyester textile & steel spiral

TECHNICAL DATA

CODE	Ø INT.	Ø OUT.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOLUME
	mm	mm	g/m	bar	bar	m H2O	m3	m	m3
PW010200029000*	20	29	**475**	14	42	10	80	60	0,106
PW010250035000	25	35	**655**	12	36	10	100	60	0,146
PW010300040000	30	40	**765**	11	33	9	120	60	0,184
PW010320043000*	32	43	**890**	11	33	9	130	60	0,214
PW010350046000*	35	46	**945**	11	33	9	140	60	0,225
PW010380049000*	38	49	**1035**	10	30	9	150	30	0,198
PW010400051000	40	51	**1080**	10	30	9	160	30	0,202
PW010450058000*	45	58	**1505**	10	30	9	180	30	0,241
PW010500063000	50	63	**1685**	10	30	8	250	30	0,286
PW010600074000*	60	74	**2115**	10	30	8	300	30	0,365
PW010630077000*	63	77	**2210**	10	30	8	320	30	0,379
PW010760091000*	76	91	**2730**	10	30	7	380	30	0,603
PW010800095000*	80	95	**2825**	8	24	7	400	20	0,498
PW011020118000*	102	118	**3890**	7	21	7	510	20	0,801

DOWNLOADS

Plutone PW Datasheet

WHITEHOUSE
FLEXIBLE TUBING LTD

FAQS

What is Plutone PW?

Black hose with yellow stripe made by a special PVC-P compound, with steel helix and polyester textile reinforcement. Smooth, flexible and easy to handle, it resists at low temperatures. It can be made conductive (R<102 Ohm/m) by grounding the spiral.

What applications are listed for Plutone PW?

Application Fields: Suction and discharge of water and liquids.