



WHITEHOUSE
FLEXIBLE TUBING LTD

SATURNO L SE



Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospheric agents and most chemicals.

Application Fields: Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.

- **Temp Range:** -25 to +60°C
- **Size Range:** 19 - 203mm
- **Material:** PVC-P
- **Reinforced:** PVC spiral

[Saturno L SE Data Sheet](#)



WHITEHOUSE
FLEXIBLE TUBING LTD

TECHNICAL DATA

COVDE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT g/m	W.P. bar	B.P. bar	VACUUM m H2O	BENDING mm	COIL LGTH. m	VOL. m3
XL060190000000*	19,1	2,2	2,9	200	5	15	6	110	50	0,046
XL060200000000	20	2,2	2,9	210	5	15	6	110	50	0,048
XL060220000000*	22	2,3	3	240	5	15	6	130	50	0,061
XL060250000000	25	2,3	3	270	5	15	6	140	50	0,078
XL060255000000*	25,5	2,3	3	270	5	15	6	140	50	0,079
XL060300000000	30	2,3	3,1	320	5	15	6	170	50	0,116
XL060320000000	31,8	2,4	3,2	360	5	15	6	180	50	0,122
XL060325000000*	32,5	2,4	3,2	370	5	15	6	180	50	0,124
XL060350000000*	35	2,5	3,3	400	5	15	6	195	50	0,133
XL060380000000	38,1	2,6	3,4	450	5	15	6	210	50	0,172
XL060390000000*	39	2,6	3,4	460	5	15	6	215	50	0,176
XL060400000000	40	2,6	3,5	480	5	15	6	220	50	0,180
XL060450000000*	45	2,7	3,6	560	5	15	6	250	50	0,226
XL060500000000	50	3	4	700	5	15	6	270	50	0,251
XL060520000000	50,8	3	4	710	5	15	6	270	50	0,254
XL060515000000	51,5	3	4	720	5	15	6	270	50	0,257
XL060515000050	51,5	3	4	720	5	15	6	270	50	0,257
XL060550000000*	55	3	4	760	5	15	6	310	50	0,363
XL060570000000*	57	3	4	790	5	15	6	310	50	0,374
XL060600000000	60	3	4,2	860	5	15	6	330	50	0,394
XL060630000000	63,5	3	4,2	910	5	15	6	350	50	0,414
XL060650000000*	65	3,1	4,3	960	5	15	6	360	50	0,424
XL060700000000*	70	3,2	4,5	1040	4	12	6	450	50	0,569
XL060750000000*	75	3,3	4,6	1140	4	12	6	500	50	0,606
XL060760000000	76,2	3,3	4,6	1160	4	12	6	500	50	0,615
XL060800000000	80	3,6	5	1330	4	12	6	550	50	0,648
XL060800000036	80	3,6	5	1330	4	12	6	550	50	0,648
XL060900000000*	90	4,2	6	1840	3	9	6	630	30	0,588
XL061000000000	100	4,6	6,4	2180	3	9	6	710	30	0,866
XL061020000000	102	4,6	6,4	2220	3	9	6	710	30	0,882
XL061100000000*	110	5	6,7	2530	3	9	6	720	30	1,264
XL061200000000*	120	5	6,8	2770	3	9	6	730	30	1,368
XL061250000000*	125	5,1	6,9	2950	3	9	6	740	30	1,421
XL061270000000*	127	5,1	6,9	2990	3	9	6	740	30	1,442
XL061500000000*	151,5	5,9	7,8	4100	3	9	6	800	20	1,337
XL061520000000*	152,4	5,9	7,8	4120	3	9	6	800	20	1,344
XL062000000000*	200	6,5	10	6420	2	6	4,5	1000	10	1,760
XL062030000000*	203,2	6,5	10	6520	2	6	4,5	1000	10	1,786



WHITEHOUSE
FLEXIBLE TUBING LTD

DOWNLOADS

[Saturno L SE Datasheet](#)