WHITEHOUSE
FLEXIBLE TUBING LTD

# SATURNO L SE

## SATURNO L SE – FLEXIBLE HOSE AND DUCTING

Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospherical agents and most chemicals.

- Temp Range: -25 to +60°C
- Size Range: 19 - 203mm
- Material: PVC-P
- Reinforced: PVC spiral

Saturno L SE Data Sheet

WHITEHOUSE
FLEXIBLE TUBING LTD

## PRODUCT DETAILS

### Saturno L SE

Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospherical agents and most chemicals.

Application Fields: Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.

Temp Range: -25 to +60°C

Size Range: 19 – 203mm

Material: PVC-P

Reinforced: PVC spiral

- Temp Range: -25 to +60°C
- Size Range: 19 – 203mm
- Material: PVC-P
- Reinforced: PVC spiral

## TECHNICAL DATA

| COVDE | Ø INT. | MIN WALL TH. | MAX WALL TH. | WEIGHT | W.P. | B.P. | VACUUM | BENDING | COIL LGTH. | VOL. |
|---|---|---|---|---|---|---|---|---|---|---|
| | mm | mm | mm | g/m | bar | bar | m H2O | mm | m | m3 |
| **XL060190000000*** | 19,1 | 2,2 | 2,9 | **200** | 5 | 15 | 6 | 110 | 50 | 0,046 |
| **XL060200000000** | 20 | 2,2 | 2,9 | **210** | 5 | 15 | 6 | 110 | 50 | 0,048 |
| **XL060220000000*** | 22 | 2,3 | 3 | **240** | 5 | 15 | 6 | 130 | 50 | 0,061 |
| **XL060250000000** | 25 | 2,3 | 3 | **270** | 5 | 15 | 6 | 140 | 50 | 0,078 |
| **XL060255000000*** | 25,5 | 2,3 | 3 | **270** | 5 | 15 | 6 | 140 | 50 | 0,079 |
| **XL060300000000** | 30 | 2,3 | 3,1 | **320** | 5 | 15 | 6 | 170 | 50 | 0,116 |
| **XL060320000000** | 31,8 | 2,4 | 3,2 | **360** | 5 | 15 | 6 | 180 | 50 | 0,122 |
| **XL060325000000*** | 32,5 | 2,4 | 3,2 | **370** | 5 | 15 | 6 | 180 | 50 | 0,124 |
| **XL060350000000*** | 35 | 2,5 | 3,3 | **400** | 5 | 15 | 6 | 195 | 50 | 0,133 |
| **XL060380000000** | 38,1 | 2,6 | 3,4 | **450** | 5 | 15 | 6 | 210 | 50 | 0,172 |
| **XL060390000000*** | 39 | 2,6 | 3,4 | **460** | 5 | 15 | 6 | 215 | 50 | 0,176 |
| **XL060400000000** | 40 | 2,6 | 3,5 | **480** | 5 | 15 | 6 | 220 | 50 | 0,180 |
| **XL060450000000*** | 45 | 2,7 | 3,6 | **560** | 5 | 15 | 6 | 250 | 50 | 0,226 |
| **XL060500000000** | 50 | 3 | 4 | **700** | 5 | 15 | 6 | 270 | 50 | 0,251 |
| **XL060520000000** | 50,8 | 3 | 4 | **710** | 5 | 15 | 6 | 270 | 50 | 0,254 |
| **XL060515000000** | 51,5 | 3 | 4 | **720** | 5 | 15 | 6 | 270 | 50 | 0,257 |
| **XL060515000050** | 51,5 | 3 | 4 | **720** | 5 | 15 | 6 | 270 | 50 | 0,257 |
| **XL060550000000*** | 55 | 3 | 4 | **760** | 5 | 15 | 6 | 310 | 50 | 0,363 |
| **XL060570000000*** | 57 | 3 | 4 | **790** | 5 | 15 | 6 | 310 | 50 | 0,374 |

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| **XL060600000000** | 60 | 3 | 4,2 | **860** | 5 | 15 | 6 | 330 | 50 | 0,394 |
| **XL060630000000** | 63,5 | 3 | 4,2 | **910** | 5 | 15 | 6 | 350 | 50 | 0,414 |
| **XL060650000000*** | 65 | 3,1 | 4,3 | **960** | 5 | 15 | 6 | 360 | 50 | 0,424 |
| **XL060700000000*** | 70 | 3,2 | 4,5 | **1040** | 4 | 12 | 6 | 450 | 50 | 0,569 |
| **XL060750000000*** | 75 | 3,3 | 4,6 | **1140** | 4 | 12 | 6 | 500 | 50 | 0,606 |
| **XL060760000000** | 76,2 | 3,3 | 4,6 | **1160** | 4 | 12 | 6 | 500 | 50 | 0,615 |
| **XL060800000000** | 80 | 3,6 | 5 | **1330** | 4 | 12 | 6 | 550 | 50 | 0,648 |
| **XL060800000036** | 80 | 3,6 | 5 | **1330** | 4 | 12 | 6 | 550 | 50 | 0,648 |
| **XL060900000000*** | 90 | 4,2 | 6 | **1840** | 3 | 9 | 6 | 630 | 30 | 0,588 |
| **XL061000000000** | 100 | 4,6 | 6,4 | **2180** | 3 | 9 | 6 | 710 | 30 | 0,866 |
| **XL061020000000** | 102 | 4,6 | 6,4 | **2220** | 3 | 9 | 6 | 710 | 30 | 0,882 |
| **XL061100000000*** | 110 | 5 | 6,7 | **2530** | 3 | 9 | 6 | 720 | 30 | 1,264 |
| **XL061200000000*** | 120 | 5 | 6,8 | **2770** | 3 | 9 | 6 | 730 | 30 | 1,368 |
| **XL061250000000*** | 125 | 5,1 | 6,9 | **2950** | 3 | 9 | 6 | 740 | 30 | 1,421 |
| **XL061270000000*** | 127 | 5,1 | 6,9 | **2990** | 3 | 9 | 6 | 740 | 30 | 1,442 |
| **XL061500000000*** | 151,5 | 5,9 | 7,8 | **4100** | 3 | 9 | 6 | 800 | 20 | 1,337 |
| **XL061520000000*** | 152,4 | 5,9 | 7,8 | **4120** | 3 | 9 | 6 | 800 | 20 | 1,344 |
| **XL062000000000*** | 200 | 6,5 | 10 | **6420** | 2 | 6 | 4,5 | 1000 | 10 | 1,760 |
| **XL062030000000*** | 203,2 | 6,5 | 10 | **6520** | 2 | 6 | 4,5 | 1000 | 10 | 1,786 |

## DOWNLOADS

Saturno L SE Datasheet

## FAQS

### What is Saturno L SE?

Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospherical agents and most chemicals.

### What applications are listed for Saturno L SE?

Application Fields: Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.