WHITEHOUSE
FLEXIBLE TUBING LTD

SATURNO L SE



SATURNO L SE – FLEXIBLE HOSE AND DUCTING

Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospherical agents and most chemicals.

- Temp Range: -25 to +60°C
- Size Range: 19 - 203mm
- Material: PVC-P
- Reinforced: PVC spiral

Saturno L SE Data Sheet

WHITEHOUSE
FLEXIBLE TUBING LTD

PRODUCT DETAILS

Saturno L SE

Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospherical agents and most chemicals.

Application Fields: Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.

Temp Range: -25 to +60°C

Size Range: 19 – 203mm

Material: PVC-P

Reinforced: PVC spiral

- Temp Range: -25 to +60°C
- Size Range: 19 – 203mm
- Material: PVC-P
- Reinforced: PVC spiral

TECHNICAL DATA

COVDE	Ø INT.	MIN WALL TH.	MAX WALL TH.	WEIGHT	W.P.	B.P.	VACUUM	BENDING	COIL LGTH.	VOL.
	mm	mm	mm	g/m	bar	bar	m H2O	mm	m	m3
XL060190000000*	19,1	2,2	2,9	**200**	5	15	6	110	50	0,046
XL060200000000	20	2,2	2,9	**210**	5	15	6	110	50	0,048
XL060220000000*	22	2,3	3	**240**	5	15	6	130	50	0,061
XL060250000000	25	2,3	3	**270**	5	15	6	140	50	0,078
XL060255000000*	25,5	2,3	3	**270**	5	15	6	140	50	0,079
XL060300000000	30	2,3	3,1	**320**	5	15	6	170	50	0,116
XL060320000000	31,8	2,4	3,2	**360**	5	15	6	180	50	0,122
XL060325000000*	32,5	2,4	3,2	**370**	5	15	6	180	50	0,124
XL060350000000*	35	2,5	3,3	**400**	5	15	6	195	50	0,133
XL060380000000	38,1	2,6	3,4	**450**	5	15	6	210	50	0,172
XL060390000000*	39	2,6	3,4	**460**	5	15	6	215	50	0,176
XL060400000000	40	2,6	3,5	**480**	5	15	6	220	50	0,180
XL060450000000*	45	2,7	3,6	**560**	5	15	6	250	50	0,226
XL060500000000	50	3	4	**700**	5	15	6	270	50	0,251
XL060520000000	50,8	3	4	**710**	5	15	6	270	50	0,254
XL060515000000	51,5	3	4	**720**	5	15	6	270	50	0,257
XL060515000050	51,5	3	4	**720**	5	15	6	270	50	0,257
XL060550000000*	55	3	4	**760**	5	15	6	310	50	0,363
XL060570000000*	57	3	4	**790**	5	15	6	310	50	0,374

XL060600000000	60	3	4,2	**860**	5	15	6	330	50	0,394
XL060630000000	63,5	3	4,2	**910**	5	15	6	350	50	0,414
XL060650000000*	65	3,1	4,3	**960**	5	15	6	360	50	0,424
XL060700000000*	70	3,2	4,5	**1040**	4	12	6	450	50	0,569
XL060750000000*	75	3,3	4,6	**1140**	4	12	6	500	50	0,606
XL060760000000	76,2	3,3	4,6	**1160**	4	12	6	500	50	0,615
XL060800000000	80	3,6	5	**1330**	4	12	6	550	50	0,648
XL060800000036	80	3,6	5	**1330**	4	12	6	550	50	0,648
XL060900000000*	90	4,2	6	**1840**	3	9	6	630	30	0,588
XL061000000000	100	4,6	6,4	**2180**	3	9	6	710	30	0,866
XL061020000000	102	4,6	6,4	**2220**	3	9	6	710	30	0,882
XL061100000000*	110	5	6,7	**2530**	3	9	6	720	30	1,264
XL061200000000*	120	5	6,8	**2770**	3	9	6	730	30	1,368
XL061250000000*	125	5,1	6,9	**2950**	3	9	6	740	30	1,421
XL061270000000*	127	5,1	6,9	**2990**	3	9	6	740	30	1,442
XL061500000000*	151,5	5,9	7,8	**4100**	3	9	6	800	20	1,337
XL061520000000*	152,4	5,9	7,8	**4120**	3	9	6	800	20	1,344
XL062000000000*	200	6,5	10	**6420**	2	6	4,5	1000	10	1,760
XL062030000000*	203,2	6,5	10	**6520**	2	6	4,5	1000	10	1,786

DOWNLOADS

Saturno L SE Datasheet

FAQS

What is Saturno L SE?

Transparent green PVC-P hose reinforced with an ivory anti-shock rigid PVC spiral. Inside surface smooth, light corrugation outside. Very flexible even at low temperatures. Strong, resistant to crushing, atmospherical agents and most chemicals.

What applications are listed for Saturno L SE?

Application Fields: Excellent in agriculture, for irrigation and suction of liquids; suitable to be used on slurry machines. Different colour versions available on request.