

VULCANO® PVC AF



Black PVC-P hose, reinforced with a steel spiral. Slightly corrugated inside and outside. This hose is flame retardant according to UL 94 V0. Constant wall thickness 0,6 mm. Thanks to its high mechanical features, it can be used in many applications, especially when good dynamic properties are required: flexible, light, easy to handle, really good bending. Good resistance to most chemicals, ozone, UV rays, weather conditions and ageing. The hose can be conductive ($R < 102$ Ohm/m) by grounding the spiral.

Application Fields: Ventilation and air conditioning systems, fumes and dust extraction, suction of vapours and gases.

- **Temp Range:** -10 to +60°C
- **Size Range:** 76 - 203mm
- **Material:** PVC-P
- **Reinforced:** Steel spiral

[Vulcano PVC AF Datasheet](#)



WHITEHOUSE
FLEXIBLE TUBING LTD

TECHNICAL DATA

CODE	Ø INT.	MIN WALL TH.	WEIGHT	VACUUM	BENDING	COIL LGTH.	VOL.
	mm	mm	g/m	m H2O	mm	m	m3
VP040760000000*	76	0,6	570	1,7	65	20	0,22
VP041020000000*	102	0,6	725	1,3	90	15	0,33
VP041100000000*	110	0,6	780	1,3	95	15	0,35
VP041270000000*	127	0,6	885	1	110	15	0,40
VP041500000000*	150	0,6	1045	0,8	130	15	0,71
VP042030000000*	203	0,6	1475	0,4	175	15	0,94

DOWNLOADS

[Vulcano PVC AF](#)